



Beckery Road, Glastonbury, Somerset, BA6 9NX Tel. 01458833186 Email.info@batmink.co.uk

## **VX-118S**

Product Code: VEC255



System Components Type Driver Unit Low Freq. compression driver Frequency Range(-10dB) Frequency response (-3dB) Coverage Angle Harmonic distortion Impedance ( Passive) Impedance Bi-amp(HF+MF) Rated power (Continuous/Program/Peak) LF Rated power HF Rated power System Maximum SPL<sup>3</sup>

System Sensitivity(1w@1m)

Connection Suspension

**Enclosure finish** 

Cabinet Finish Grill Perforated Dimensions(W×DxH) Net Weight Gross Weight 18" Subwoofer loudspeaker system 1x18 IN (458mm) ferrite magnet

31Hz-230Hz 35Hz-200Hz

≦0.10% 8 ohms 8 ohms 450W/900W/1800W

1600-2000W

130dB SPL peak 99dB SPL

2 × 4 Pole Speaker Connector Fly bar, tripod, pole Baltic Birch 18 mm 11-ply Plywood finished with textured Polyurethane Black DuraFlex finish Power coated,black,16-gauge perforated steel 597×749×508mm 38kg 41kg









**PRO-FLITE** PRO-STAGE

www.vector-audio.co.uk

Lumaform PRO-LINK